



Filter media – selecting the right needle

Groz-Beckert – Partner to the filter industry

GROZ-BECKERT

Groz-Beckert KG

Parkweg 2, 72458 Albstadt, Germany
Phone +49 7431 10-0, Fax +49 7431 10-2088
contact-felting@groz-beckert.com
www.groz-beckert.com

To produce needled filtration media, needles with different barbs and working parts should be used depending on the intended application. In keeping with the requirements of customers from the filtration industry and adapted to the properties specified for the final product, a range of different needle types are available for selection from the Groz-Beckert portfolio of felting needles.

Benefits:

- Cost-efficient production
- Process stability
- Longer service life
- Optimum surface quality of the end product
- Improved tear strength
- Efficient needling

Depending on the end application, different product characteristics are required by filter felt manufacturers. This is reflected in the choice of plant system configuration.




Filter hose




Selection and properties of felting needles

Standard felting needle – cost efficiency




The use of RF barbs ensures a high level of process stability for the complete needling process without escalating costs.

GEBECON™/felting needles – process stability



GEBECON™ felting needles used for pre-needling offer the perfect combination of good surface properties in the end product and optimum bending strength.

EcoStar™ – high surface quality




GEBECON™ felting needles used for pre-needling offer the perfect combination of good surface properties in the end product and optimum bending strength. The use of EcoStar™ felting needles for intermediate and finish needling results in the best possible surface quality.

Teardrop shaped working part/HL barbs – high tensile strength



Felting needles with a teardrop shaped working part cross-section and HL barbs over the whole needling effect enable products to be manufactured causing minimal stress to the fibers and low damage to the support fabric.

Twisted – efficiency



The twisted working part of a Twisted felting needle ensures greater barb definition in application. The result: more efficient intermediate and finish needling and consequently capacity for higher production speeds.

GEBECON™/GEBEDUR™ II – process stability/longer service life



GEBECON™ felting needles used for pre-needling offer the perfect combination of good surface properties in the end product and optimum bending strength. Treating the felting needles with GEBEDUR™ II over the complete needling process guarantees an extended service life and consequently a uniform needling effect for the whole application period.